



MATERIAL SAFETY DATA SHEET

Section 1 -- PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NUMBER PS-7500  
PRODUCT NAME Universal Overall Clearcoat  
MANUFACTURER'S NAME Teknol, Inc.  
2650 Nordic Road  
Dayton, OH 45414  
www.performerseries.com

HMIS CODES Health 2  
Flammability 2  
Reactivity 1  
PPE G

Emergency Phone: (800) 424-9300  
Information Phone: (937) 280-0085  
Fax Number: (937) 264-7844

Date: 08/28/2007

Section 2 -- COMPOSITION/INFORMATION ON HAZARDOUS INGREDIENTS

% by WT	CAS No.	INGREDIENT UNITS	VAPOR PRESSURE
5-20	67-64-1	Acetone	185
1-5	1317-95-9	Methyl n-Amyl Ketone	2.2
<1	64742-89-8	Aliphatic Naphtha	5.2
5-20	1330-20-7	Xylene	9.5
20-50	98-56-6	PCBTF	5.3
1-5	100-41-4	Ethylbenzene	1.3
<1	77-58-7	Disbutyltin Dilaurate	<1
<1	96-48-0	Butyrolactone	3.2
5-20	624-54-4	Pentyl Propionate	2

Section 3 -- HAZARDS IDENTIFICATION

ROUTES OF EXPOSURE:  
Exposure may be by INHALATION and/or SKIN or EYE contact, depending on conditions of use. To minimize exposure, follow recommendations for proper use, ventilation, and personal protective equipment.

EFFECTS OF OVEREXPOSURE:  
Irritation of eyes, skin and upper respiratory system. May cause nervous system depression. Extreme overexposure may result in unconsciousness and possibly death.

SIGNS AND SYMPTOMS OF OVEREXPOSURE:  
Headache, dizziness, nausea, and loss of coordination are indications of excessive exposure to vapors or spray mists. Redness and itching or burning sensation may indicate eye or excessive skin exposure.

MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE:  
None generally recognized.

CANCER INFORMATION:  
FOR COMPLETE DISCUSSION OF TOXICOLOGY DATA REFER TO SECTION 11.

Section 4 -- FIRST AID MEASURES

Wash affected area thoroughly with soap and water. Remove contaminated clothing and launder before re-use.

If in EYES:  
Flush eyes with large amounts of water for 15 minutes. Get medical attention.

If SWALLOWED:  
Do not induce vomiting. Get medical attention immediately.

Section 5 -- FIRE FIGHTING MEASURES

FLASH POINT -20°F  
LEL 0.1%  
UEL 12.8%

EXTINGUISHING MEDIA:  
Use National Fire Protection Association (NFPA) Class B extinguishers (carbon dioxide, dry chemical, or universal aqueous film forming foam) designed to extinguish NFPA Class IB flammable liquid fires. Water spray may be ineffective. Water spray may be used to cool closed containers to prevent pressure build-up and possible auto ignition or explosion when exposed to extreme heat.

UNUSUAL FIRE AND EXPLOSION HAZARDS:

Containers may explode when exposed to extreme heat. Application to hot surfaces requires special precautions.

During emergency conditions overexposure to decomposition products may cause a health hazard. Symptoms may not be immediately apparent. Obtain medical attention.

**SPECIAL FIRE FIGHTING PROCEDURES:**

Full protective equipment including self-contained breathing apparatus should be used. Water spray may be ineffective. If water is used, fog nozzles are preferable. Water may be used to cool closed containers to prevent pressure build-up and possible auto ignition or explosion when exposed to extreme heat.

=====  
**Section 6 -- ACCIDENTAL RELEASE MEASURES**  
=====

**STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED:**

Provide maximum ventilation. Only personnel equipped with proper respiratory, skin, and eye protection should be permitted in the area. Remove all sources of ignition. Take up spilled material with sand, vermiculite, or other noncombustible absorbent material and place in clean, empty containers for disposal. Only the spilled material and the absorbent should be placed in this container.

=====  
**Section 7 -- HANDLING RELEASE MEASURES**  
=====

**PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE:**

Keep away from heat, sparks, and open flame. Vapors will accumulate readily and may ignite explosively. During use and until all vapors are gone: Keep area ventilated - Do not smoke - Extinguish all flames, pilot lights, and heaters - Turn off stoves, electric tools and appliances, and other sources of ignition. Consult NFPA Code. Use approved bonding and grounding procedures. Contents under pressure. Do not puncture, incinerate, or expose to temperature above 120F. Heat from sunlight, radiators, stoves, hot water, and other heat sources could cause container to burst. Do not take internally. Keep out of the reach of children.

=====  
**Section 8 -- EXPOSURE CONTROLS / PERSONAL PROTECTION**  
=====

**PRECAUTIONS TO BE TAKEN IN USE:**

Use only with adequate ventilation. Avoid contact with skin and eyes. Avoid breathing vapor and spray mist. Wash hands after using. This coating may contain materials classified as nuisance particulates (listed "as Dust" in section 2) which may be present at hazardous levels only during sanding or abrading of the dried film. If no specific dusts are listed in section 2, the applicable limits for nuisance dust ar ACGIII TLV 10 mg/m3 (total dust), 3 mg/m3 respirable fraction), OSHA PEL 15 mg/m3 (total dust), 5 mg/m3 (respirable fraction). Removal of old paint by sanding, scraping, or other means may generate dust or fumes that contain lead.

**VENTILATION:**

Local exhaust preferable. General exhaust acceptable if the exposure to materials in section 2 is maintained below applicable exposure limits. Refer to OSHA Standards 1910.94, 1910.107, 1910.108.

**RESPIRATORY PROTECTION:**

If personal exposure cannot be controlled below applicable limits by ventilation, wear a properly fitted organic vapor/particulate respirator approved by NIOSH/MSHA for protection against materials in section 2. When sanding or abrading the dried film, wear a dust/mist respirator approved by NIOSH/MSHA for dust which may be generated from this product, underlying paint, or the abrasive.

**PROTECTIVE GLOVES:**

None required for normal application of aerosol products where minimal skin contact is expected. For long repeated contact, wear chemical resistant gloves.

**EYE PROTECTION:**

Wear safety spectacles with unperforated sideshields.

**OTHER PRECAUTIONS:**

Intentional misuse by deliberately concentrating and inhaling the contents can be harmful of fatal.

=====  
**Section 9 -- PHYSICAL AND CHEMICAL PROPERTIES**  
=====

PRODUCT WEIGHT	8.681 lb/gal	1135 g/l
SPECIFIC GRAVITY	1.040	
BOILING POINT	0-365°F	-17-185°C
VOLATILES	65.6% % by Wt	66.5 % by Vol
EVAPORATION RATE	Same as ether	
VAPOR DENSITY	Heavier than air	
COATING VOC	4.29 lb/gal	514 g/l
MATERIAL VOC	3.03 lb/gal	363 g/l

=====  
**Section 10 -- STABILITY AND REACTIVITY**  
=====

**STABILITY:**

This product is normally stable and will not undergo hazardous reactions.

**CONDITIONS TO AVOID:**

None Known.

**INCOMPATIBILITY:**

Avoid contact with strong alkalies, strong mineral acids, or strong oxidizing agents.

**HAZARDOUS DECOMPOSITION PRODUCTS:**

Carbon monoxide, carbon dioxide, oxides of sulfur, oxides of barium, lower molecular weight polymer fractions.

**HAZARDOUS POLYMERIZATION:**

None Known.

=====  
**Section 11 -- TOXICOLOGICAL INFORMATION**  
=====

CAS No.	Ingredient Name	LC50	RAT	4 HR	N/E
67-64-1	Acetone	LD50	RAT		5800 MG/KG
110-43-0	Methyl n-Amyl Ketone	LC50	RAT	4HR	2000-4000 PPM
		LD50	RAT		1600 MG/KG
64742-89-8	Aliphatic Naphtha	LC50	RAT	4HR	3400 PPM
		LD50	RAT		8 ML/KG
1330-20-7	Xylene	LC50	RAT	4HR	5000 PPM
		LD50	RAT		4300 MG/KG
98-56-6	PCBTF	LC50	RAT	4HR	22000 MG/L
		LD50			13000MG/KG
100-41-4	Ethylbenzene	LC50	RAT	4HR	N/E
		LD50			3500 MG/KG
77-58-7	Dibutyltin Dilaurate	LC50	RAT	4HR	N/E
		LD50			175 MG/KG
96-48-0	Butyrolactone	LC50	RAT	4HR	N/E
		LD50			1540 MG/KG
624-54-4	Pentyl Propionate	LC50	RAT	4HR	15000 PPM
		LD50			14 G/KG

=====  
**Section 12 -- ECOLOGICAL INFORMATION**  
=====

ECOTOXICOLOGICAL INFORMATION:

ECOTOXICITY: N/E

ENVIRONMENTAL FATE:

MOBILITY: N/E

BIODEGRADATION: N/E

BIOACCUMULATION: N/E

PHYSICAL/CHEMICAL:

HYDROLYSIS: N/E

PHOTOLYSIS: N/E

=====  
**Section 13 -- DISPOSAL CONSIDERATIONS**  
=====

WASTE DISPOSAL METHOD:

Waste from this product may be hazardous as defined under the Resource Conservation and Recovery Act (RCRA) 40 CFR 261. Do not incinerate. Depressurize container. Dispose of in accordance with Federal, State, and Local regulations regarding pollution.

=====  
**Section 14 -- TRANSPORT INFORMATION**  
=====

Proper Shipping Name: Consumer Commodity

NOS Technical Name: ORM-D

Hazard Class: N/A

UN Number: UN N/A

Packing Group: N/A

=====  
**Section 15 -- REGULATORY INFORMATION**  
=====

SARA 313:

CAS No.	CHEMICAL/COMPOUND	% by WT
1330-20-7	Xylene	17.8
100-41-4	Ethylbenzene	4.1
624-54-4	Pentyl Propionate	10.0

CALIFORNIA PROPOSITION 65

WARNING: This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm.

TSCA CERTIFICATION:

U.S. TSCA: This product and/or all of its components are listed on the U.S. TSCA Inventory or is otherwise exempt from TSCA Inventory reporting requirements.

=====  
**Section 16 -- OTHER INFORMATION**  
=====

DISCLAIMER:

Do not handle until the manufacturer's safety precautions have been read and understood. Regulations require that all employees be trained on Material Safety Data Sheets for all products with which they come in contact. While we believe that the data contained herein is accurate and derived from qualified sources, the data are not to be taken as a warranty or representation for which we assume legal responsibility. They are offered solely for your consideration, investigation, and verification. Any use of these data and information must be determined by the user to be in accordance with applicable federal, state, provincial, and local laws and regulations.

## ENVIRONMENTAL DATA SHEET

Teknol, Inc.  
2650 Nordic Road  
Dayton, Oh 45414  
[www.performerseries.com](http://www.performerseries.com)

All data given below are MAXIMUM THEORETICAL VALUES based on the product AS CURRENTLY FORMULATED. Variations may occur on individual batches due to adjustments made during production.

### PRODUCT NUMBER

PS-7500

### PRODUCT NAME

Universal Overall Clearcoat

### PRODUCT WEIGHT

8.681 lb/gal

### SPECIFIC GRAVITY

1.040

### FLASH POINT

-20-327°F

### VOLATILE ORGANIC COMPOUNDS

A. Coating Density	8.68 lb/gal	1041 g/l
B. Total Volatiles	65.7 % by Wt	66.6 % by Vol.
C. Organic Volatiles	34.9 % by Wt	37.1 % by Vol.
D. Percent Non-Volatile	34.3 % by Wt	33.4 % by Vol.
E. Coating VOC	4.29 lb/gal	514 g/l
Material VOC	3.03 lb/gal	363 g/l
Solids	2.98 lb/gal	357 g/l

### WASTE DISPOSAL

Waste from this product may be hazardous as defined under the Resource Conservation and Recovery Act (RCRA) 40 CFR 261. Waste must be tested for ignitability to determine the applicable EPA hazardous waste numbers. The addition of reducers or other additives to this product may substantially alter the above data. Since conditions of use are outside our control, we make no warranties, express or implied, and assume no liability in connection with any use of this information.