

## 1. Identification

**Product identifier** 2K Catalyzed Urethane Primer Surfacer

**Other means of identification**

**Product code** PS-4900

**Recommended use** Primer

**Recommended restrictions** No other uses are advised.

**Manufacturer/Importer/Supplier/Distributor information**

**Manufacturer**

**Company name** Teknol, Inc.

**Address** 2650 Nordic Rd.  
Dayton, OH 45414  
United States

**Telephone** (937) 264-7844 Technical Contact, Sales  
(937) 280-0085 Fax

**Website** www.performerseries.com

**E-mail** Not available.

**Emergency phone number** Chemtrec: 800-424-9300

## 2. Hazard(s) identification

**Physical hazards** Flammable liquids Category 2

**Health hazards** Acute toxicity, oral Category 4  
Acute toxicity, dermal Category 4  
Skin corrosion/irritation Category 2  
Serious eye damage/eye irritation Category 2A  
Carcinogenicity Category 1A  
Reproductive toxicity Category 2  
Specific target organ toxicity, repeated exposure Category 1  
Aspiration hazard Category 1

**Environmental hazards** Hazardous to the aquatic environment, acute hazard Category 2  
Hazardous to the aquatic environment, long-term hazard Category 2

**OSHA defined hazards** Not classified.

### Label elements



**Signal word** Danger

**Hazard statement** Highly flammable liquid and vapor. Harmful if swallowed. May be fatal if swallowed and enters airways. Harmful in contact with skin. Causes skin irritation. Causes serious eye irritation. May cause cancer. Suspected of damaging fertility or the unborn child. Causes damage to organs through prolonged or repeated exposure. Toxic to aquatic life with long lasting effects.

## Precautionary statement

### Prevention

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Keep container tightly closed. Ground/bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Do not breathe mist or vapor. Wash thoroughly after handling. Do not eat, drink or smoke when using this product. Avoid release to the environment. Wear protective gloves/protective clothing/eye protection/face protection.

### Response

If swallowed: Immediately call a poison center/doctor. Rinse mouth. Do NOT induce vomiting. If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If exposed or concerned: Get medical advice/attention. Call a poison center/doctor if you feel unwell. If skin irritation occurs: Get medical advice/attention. If eye irritation persists: Get medical advice/attention. Take off contaminated clothing and wash before reuse. In case of fire: Use appropriate media to extinguish. Collect spillage.

### Storage

Store in a well-ventilated place. Keep cool. Store locked up.

### Disposal

Dispose of contents/container in accordance with local/regional/national/international regulations.

### Hazard(s) not otherwise classified (HNOC)

Static accumulating flammable liquid can become electrostatically charged even in bonded and grounded equipment. Sparks may ignite liquid and vapor. May cause flash fire or explosion.

### Supplemental information

48.38% of the mixture consists of component(s) of unknown acute oral toxicity. 54.08% of the mixture consists of component(s) of unknown acute dermal toxicity. % of the mixture consists of component(s) of unknown acute inhalation toxicity. 44.08% of the mixture consists of component(s) of unknown acute hazards to the aquatic environment. 44.08% of the mixture consists of component(s) of unknown long-term hazards to the aquatic environment.

## 3. Composition/information on ingredients

### Mixtures

Chemical name	Common name and synonyms	CAS number	%
Talc		14807-96-6	20 - < 30
Xylene		1330-20-7	20 - < 30
Barium Sulfate		7727-43-7	10 - < 20
Toluene		108-88-3	10 - < 20
Ethylbenzene		100-41-4	5 - < 10
Glycol Ether PM Acetate		108-65-6	5 - < 10
Methyl Acetate		79-20-9	5 - < 10
Titanium Dioxide		13463-67-7	5 - < 10
Silica		7631-86-9	< 1
Silicon Dioxide (as Amorphous Silica; See Silica), Particulate		112945-52-5	< 1
Styrene		100-42-5	< 1
Tremolite (Non-asbestiform)		14567-73-8	< 1
Carbon Black		1333-86-4	< 0.2
Crystalline Quartz		14808-60-7	< 0.2
Isobutyl Acetate		110-19-0	< 0.1
Isobutyl Alcohol		78-83-1	< 0.1
Mineral Spirits		8052-41-3	< 0.1
N-Butyl Alcohol		71-36-3	< 0.1
Phosphoric Acid Regulatory		7664-38-2	< 0.1

\*Designates that a specific chemical identity and/or percentage of composition has been withheld as a trade secret.

## 4. First-aid measures

### Inhalation

Move to fresh air. Call a physician if symptoms develop or persist.

### Skin contact

Take off immediately all contaminated clothing. Rinse skin with water/shower. Get medical advice/attention if you feel unwell. If skin irritation occurs: Get medical advice/attention. Wash contaminated clothing before reuse.

<b>Eye contact</b>	Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.
<b>Ingestion</b>	Call a physician or poison control center immediately. Rinse mouth. Do not induce vomiting. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs.
<b>Most important symptoms/effects, acute and delayed</b>	Aspiration may cause pulmonary edema and pneumonitis. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Skin irritation. May cause redness and pain. Prolonged exposure may cause chronic effects.
<b>Indication of immediate medical attention and special treatment needed</b>	Provide general supportive measures and treat symptomatically. Thermal burns: Flush with water immediately. While flushing, remove clothes which do not adhere to affected area. Call an ambulance. Continue flushing during transport to hospital. Keep victim warm. Keep victim under observation. Symptoms may be delayed.
<b>General information</b>	Take off all contaminated clothing immediately. IF exposed or concerned: Get medical advice/attention. If you feel unwell, seek medical advice (show the label where possible). Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Show this safety data sheet to the doctor in attendance. Wash contaminated clothing before reuse.

## 5. Fire-fighting measures

<b>Suitable extinguishing media</b>	Water fog. Foam. Carbon dioxide (CO <sub>2</sub> ). Dry chemical powder, carbon dioxide, sand or earth may be used for small fires only.
<b>Unsuitable extinguishing media</b>	Do not use water jet as an extinguisher, as this will spread the fire.
<b>Specific hazards arising from the chemical</b>	Vapors may form explosive mixtures with air. Vapors may travel considerable distance to a source of ignition and flash back. This product is a poor conductor of electricity and can become electrostatically charged. If sufficient charge is accumulated, ignition of flammable mixtures can occur. To reduce potential for static discharge, use proper bonding and grounding procedures. This liquid may accumulate static electricity when filling properly grounded containers. Static electricity accumulation may be significantly increased by the presence of small quantities of water or other contaminants. Material will float and may ignite on surface of water. During fire, gases hazardous to health may be formed.
<b>Special protective equipment and precautions for firefighters</b>	Self-contained breathing apparatus and full protective clothing must be worn in case of fire.
<b>Fire fighting equipment/instructions</b>	In case of fire and/or explosion do not breathe fumes. Move containers from fire area if you can do so without risk.
<b>Specific methods</b>	Use standard firefighting procedures and consider the hazards of other involved materials.
<b>General fire hazards</b>	Highly flammable liquid and vapor.

## 6. Accidental release measures

<b>Personal precautions, protective equipment and emergency procedures</b>	Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Wear appropriate protective equipment and clothing during clean-up. Do not breathe mist or vapor. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Use appropriate containment to avoid environmental contamination. Transfer by mechanical means such as vacuum truck to a salvage tank or other suitable container for recovery or safe disposal. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.
<b>Methods and materials for containment and cleaning up</b>	<p>Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material. Take precautionary measures against static discharge. Use only non-sparking tools. Prevent product from entering drains.</p> <p>Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Use a non-combustible material like vermiculite, sand or earth to soak up the product and place into a container for later disposal. Following product recovery, flush area with water.</p> <p>Small Spills: Absorb with earth, sand or other non-combustible material and transfer to containers for later disposal. Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.</p> <p>Never return spills to original containers for re-use. Put material in suitable, covered, labeled containers. For waste disposal, see section 13 of the SDS.</p>
<b>Environmental precautions</b>	Avoid release to the environment. Inform appropriate managerial or supervisory personnel of all environmental releases. Prevent further leakage or spillage if safe to do so. Avoid discharge into drains, water courses or onto the ground. Use appropriate containment to avoid environmental contamination.

## 7. Handling and storage

### Precautions for safe handling

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not handle, store or open near an open flame, sources of heat or sources of ignition. Protect material from direct sunlight. Explosion-proof general and local exhaust ventilation. Minimize fire risks from flammable and combustible materials (including combustible dust and static accumulating liquids) or dangerous reactions with incompatible materials. Handling operations that can promote accumulation of static charges include but are not limited to: mixing, filtering, pumping at high flow rates, splash filling, creating mists or sprays, tank and container filling, tank cleaning, sampling, gauging, switch loading, vacuum truck operations. Take precautionary measures against static discharges. All equipment used when handling the product must be grounded. Use non-sparking tools and explosion-proof equipment. Do not breathe mist or vapor. Do not taste or swallow. Avoid contact with eyes, skin, and clothing. Avoid prolonged exposure. When using, do not eat, drink or smoke. Pregnant or breastfeeding women must not handle this product. Should be handled in closed systems, if possible. Wear appropriate personal protective equipment. Wash hands thoroughly after handling. Avoid release to the environment. Wash contaminated clothing before reuse. Observe good industrial hygiene practices.

For additional information on equipment bonding and grounding, refer to the Canadian Electrical Code in Canada, (CSA C22.1), or the American Petroleum Institute (API) Recommended Practice 2003, "Protection Against Ignitions Arising out of Static, Lightning, and Stray Currents" or National Fire Protection Association (NFPA) 77, "Recommended Practice on Static Electricity" or National Fire Protection Association (NFPA) 70, "National Electrical Code".

### Conditions for safe storage, including any incompatibilities

Store locked up. Keep away from heat, sparks and open flame. Prevent electrostatic charge build-up by using common bonding and grounding techniques. Eliminate sources of ignition. Avoid spark promoters. Ground/bond container and equipment. These alone may be insufficient to remove static electricity. Store in a cool, dry place out of direct sunlight. Store in original tightly closed container. Store in a well-ventilated place. Keep in an area equipped with sprinklers. Store away from incompatible materials (see Section 10 of the SDS).

## 8. Exposure controls/personal protection

### Occupational exposure limits

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit. At this time, the other constituents have no known exposure limits.

#### US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Components	Type	Value
Tremolite (Non-asbestiform) (CAS 14567-73-8)	STEL	1 fibers/cm3
	TWA	0.1 fibers/cm3

#### US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Components	Type	Value	Form
Barium Sulfate (CAS 7727-43-7)	PEL	5 mg/m3	Respirable fraction.
		15 mg/m3	Total dust.
Carbon Black (CAS 1333-86-4)	PEL	3.5 mg/m3	
Crystalline Quartz (CAS 14808-60-7)	PEL	0.05 mg/m3	
Ethylbenzene (CAS 100-41-4)	PEL	435 mg/m3	
Methyl Acetate (CAS 79-20-9)	PEL	100 ppm	
		610 mg/m3	
Titanium Dioxide (CAS 13463-67-7)	PEL	200 ppm	
Xylene (CAS 1330-20-7)	PEL	15 mg/m3	Total dust.
		435 mg/m3	
		100 ppm	

#### US. OSHA Table Z-2 (29 CFR 1910.1000)

Components	Type	Value
Styrene (CAS 100-42-5)	Ceiling	200 ppm
	TWA	100 ppm
Toluene (CAS 108-88-3)	Ceiling	300 ppm

**US. OSHA Table Z-2 (29 CFR 1910.1000)**

Components	Type	Value
	TWA	200 ppm

**US. OSHA Table Z-3 (29 CFR 1910.1000)**

Components	Type	Value	Form
Barium Sulfate (CAS 7727-43-7)	TWA	5 mg/m3	Respirable fraction.
		15 mg/m3	Total dust.
		50 mppcf	Total dust.
		15 mppcf	Respirable fraction.
Crystalline Quartz (CAS 14808-60-7)	TWA	0.1 mg/m3	Respirable.
		2.4 mppcf	Respirable.
Talc (CAS 14807-96-6)	TWA	0.3 mg/m3	Total dust.
		0.1 mg/m3	Respirable.
		20 mppcf	
		2.4 mppcf	Respirable.
Titanium Dioxide (CAS 13463-67-7)	TWA	5 mg/m3	Respirable fraction.
		15 mg/m3	Total dust.
		50 mppcf	Total dust.
		15 mppcf	Respirable fraction.

**US. ACGIH Threshold Limit Values**

Components	Type	Value	Form
Barium Sulfate (CAS 7727-43-7)	TWA	5 mg/m3	Inhalable fraction.
Carbon Black (CAS 1333-86-4)	TWA	3 mg/m3	Inhalable fraction.
Crystalline Quartz (CAS 14808-60-7)	TWA	0.025 mg/m3	Respirable fraction.
Ethylbenzene (CAS 100-41-4)	TWA	20 ppm	
Methyl Acetate (CAS 79-20-9)	STEL	250 ppm	
	TWA	200 ppm	
Styrene (CAS 100-42-5)	STEL	40 ppm	
	TWA	20 ppm	
Talc (CAS 14807-96-6)	TWA	2 mg/m3	Respirable fraction.
Titanium Dioxide (CAS 13463-67-7)	TWA	10 mg/m3	
Toluene (CAS 108-88-3)	TWA	20 ppm	
Tremolite (Non-asbestiform) (CAS 14567-73-8)	TWA	0.1 fibers/cm3	Fiber.
Xylene (CAS 1330-20-7)	STEL	150 ppm	
	TWA	100 ppm	

**US. NIOSH: Pocket Guide to Chemical Hazards**

Components	Type	Value	Form
Barium Sulfate (CAS 7727-43-7)	TWA	5 mg/m3	Respirable.
		10 mg/m3	Total
Carbon Black (CAS 1333-86-4)	TWA	0.1 mg/m3	
Crystalline Quartz (CAS 14808-60-7)	TWA	0.05 mg/m3	Respirable dust.
Ethylbenzene (CAS 100-41-4)	STEL	545 mg/m3	
		125 ppm	
	TWA	435 mg/m3	
		100 ppm	
Methyl Acetate (CAS 79-20-9)	STEL	760 mg/m3	

**US. NIOSH: Pocket Guide to Chemical Hazards**

Components	Type	Value	Form
Styrene (CAS 100-42-5)	TWA	250 ppm	Respirable.
		610 mg/m3	
		200 ppm	
	STEL	425 mg/m3	
		100 ppm	
		215 mg/m3	
Talc (CAS 14807-96-6)	TWA	50 ppm	Respirable.
Toluene (CAS 108-88-3)	STEL	2 mg/m3	
		560 mg/m3	
	TWA	150 ppm	
		375 mg/m3	
		100 ppm	

**US. Workplace Environmental Exposure Level (WEEL) Guides**

Components	Type	Value
Glycol Ether PM Acetate (CAS 108-65-6)	TWA	50 ppm

**Biological limit values**
**ACGIH Biological Exposure Indices**

Components	Value	Determinant	Specimen	Sampling Time
Ethylbenzene (CAS 100-41-4)	0.15 g/g	Sum of mandelic acid and phenylglyoxylic acid	Creatinine in urine	*
Styrene (CAS 100-42-5)	40 µg/l	Styrene	Urine	*
	400 mg/g	Mandelic acid plus phenylglyoxylic acid	Creatinine in urine	*
Toluene (CAS 108-88-3)	0.3 mg/g	o-Cresol, with hydrolysis	Creatinine in urine	*
	0.03 mg/l	Toluene	Urine	*
	0.02 mg/l	Toluene	Blood	*
Xylene (CAS 1330-20-7)	1.5 g/g	Methylhippuric acids	Creatinine in urine	*

\* - For sampling details, please see the source document.

**Exposure guidelines**
**US - California OELs: Skin designation**

Glycol Ether PM Acetate (CAS 108-65-6)	Can be absorbed through the skin.
Styrene (CAS 100-42-5)	Can be absorbed through the skin.
Toluene (CAS 108-88-3)	Can be absorbed through the skin.

**US - Minnesota Haz Subs: Skin designation applies**

Styrene (CAS 100-42-5)	Skin designation applies.
Toluene (CAS 108-88-3)	Skin designation applies.

**Appropriate engineering controls**

Explosion-proof general and local exhaust ventilation. Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Provide eyewash station. Eye wash fountain and emergency showers are recommended.

**Individual protection measures, such as personal protective equipment**

**Eye/face protection** Chemical respirator with organic vapor cartridge and full facepiece.

**Skin protection**

**Hand protection** Wear appropriate chemical resistant gloves.

**Other** Wear appropriate chemical resistant clothing. Use of an impervious apron is recommended.

**Respiratory protection** Chemical respirator with organic vapor cartridge and full facepiece.

**Thermal hazards**

Wear appropriate thermal protective clothing, when necessary.

**General hygiene considerations**

Observe any medical surveillance requirements. When using do not smoke. Keep away from food and drink. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

## 9. Physical and chemical properties

**Appearance**

**Physical state** Liquid.

**Form** Liquid.

**Color** Grey

**Odor** Solvent.

**Odor threshold** Not available.

**pH** Not available.

**Melting point/freezing point** -144.4 °F (-98 °C) estimated

**Initial boiling point and boiling range** 134.24 °F (56.8 °C) estimated

**Flash point** 14.0 °F (-10.0 °C) estimated

**Evaporation rate** Not available.

**Flammability (solid, gas)** Not applicable.

**Upper/lower flammability or explosive limits**

**Flammability limit - lower (%)** 1.2 % estimated

**Flammability limit - upper (%)** 16 % estimated

**Explosive limit - lower (%)** Not available.

**Explosive limit - upper (%)** Not available.

**Vapor pressure** 408.64 hPa estimated

**Vapor density** Not available.

**Relative density** Not available.

**Solubility(ies)**

**Solubility (water)** Not available.

**Partition coefficient (n-octanol/water)** Not available.

**Auto-ignition temperature** 810 °F (432.22 °C) estimated

**Decomposition temperature** Not available.

**Viscosity** Not available.

**Other information**

**Density** 2.04 g/cm<sup>3</sup> estimated

**Explosive properties** Not explosive.

**Flammability class** Flammable IB estimated

**Oxidizing properties** Not oxidizing.

**Percent volatile** 47.94 % estimated

**Specific gravity** 2.04 estimated

## 10. Stability and reactivity

**Reactivity** The product is stable and non-reactive under normal conditions of use, storage and transport.

**Chemical stability** Material is stable under normal conditions.

<b>Possibility of hazardous reactions</b>	Hazardous polymerization does not occur.
<b>Conditions to avoid</b>	Avoid heat, sparks, open flames and other ignition sources. Avoid temperatures exceeding the flash point. Contact with incompatible materials.
<b>Incompatible materials</b>	Strong acids. Strong oxidizing agents. Nitrates. Aluminum. Halogens. Phosphorus.
<b>Hazardous decomposition products</b>	No hazardous decomposition products are known.

## 11. Toxicological information

### Information on likely routes of exposure

<b>Inhalation</b>	May cause damage to organs through prolonged or repeated exposure by inhalation.
<b>Skin contact</b>	Harmful in contact with skin. Causes skin irritation.
<b>Eye contact</b>	Causes serious eye irritation.
<b>Ingestion</b>	Harmful if swallowed. Droplets of the product aspirated into the lungs through ingestion or vomiting may cause a serious chemical pneumonia.
<b>Symptoms related to the physical, chemical and toxicological characteristics</b>	Aspiration may cause pulmonary edema and pneumonitis. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Skin irritation. May cause redness and pain.

### Information on toxicological effects

<b>Acute toxicity</b>	May be fatal if swallowed and enters airways. Harmful in contact with skin.
-----------------------	---

Components	Species	Test Results
Ethylbenzene (CAS 100-41-4)		
<b><u>Acute</u></b>		
<b>Oral</b>		
LD50	Rat	3500 mg/kg
Styrene (CAS 100-42-5)		
<b><u>Acute</u></b>		
<b>Oral</b>		
LD50	Rat	1 g/kg
Xylene (CAS 1330-20-7)		
<b><u>Acute</u></b>		
<b>Oral</b>		
LD50	Rat	3523 - 8600 mg/kg

\* Estimates for product may be based on additional component data not shown.

<b>Skin corrosion/irritation</b>	Causes skin irritation.
<b>Serious eye damage/eye irritation</b>	Causes serious eye irritation.

### Respiratory or skin sensitization

<b>Respiratory sensitization</b>	Not a respiratory sensitizer.
<b>Skin sensitization</b>	This product is not expected to cause skin sensitization.

<b>Germ cell mutagenicity</b>	No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.
-------------------------------	--

<b>Carcinogenicity</b>	May cause cancer.
------------------------	-------------------

### IARC Monographs. Overall Evaluation of Carcinogenicity

Carbon Black (CAS 1333-86-4)	2B Possibly carcinogenic to humans.
Crystalline Quartz (CAS 14808-60-7)	1 Carcinogenic to humans.
Ethylbenzene (CAS 100-41-4)	2B Possibly carcinogenic to humans.
Styrene (CAS 100-42-5)	2B Possibly carcinogenic to humans.
Talc (CAS 14807-96-6)	2B Possibly carcinogenic to humans.
	3 Not classifiable as to carcinogenicity to humans.
Titanium Dioxide (CAS 13463-67-7)	2B Possibly carcinogenic to humans.
Toluene (CAS 108-88-3)	3 Not classifiable as to carcinogenicity to humans.
Tremolite (Non-asbestiform) (CAS 14567-73-8)	1 Carcinogenic to humans.
Xylene (CAS 1330-20-7)	3 Not classifiable as to carcinogenicity to humans.



**OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)**

Tremolite (Non-asbestiform) (CAS 14567-73-8) Cancer

**US. National Toxicology Program (NTP) Report on Carcinogens**

Crystalline Quartz (CAS 14808-60-7) Known To Be Human Carcinogen.

Styrene (CAS 100-42-5) Reasonably Anticipated to be a Human Carcinogen.

Tremolite (Non-asbestiform) (CAS 14567-73-8) Known To Be Human Carcinogen.

**Reproductive toxicity** Components in this product have been shown to cause birth defects and reproductive disorders in laboratory animals. Suspected of damaging fertility or the unborn child.**Specific target organ toxicity - single exposure** Not classified.**Specific target organ toxicity - repeated exposure** Causes damage to organs through prolonged or repeated exposure.**Aspiration hazard** May be fatal if swallowed and enters airways.**Chronic effects** Causes damage to organs through prolonged or repeated exposure. Prolonged inhalation may be harmful. Prolonged exposure may cause chronic effects.**12. Ecological information****Ecotoxicity** Toxic to aquatic life with long lasting effects.

Components		Species	Test Results
Barium Sulfate (CAS 7727-43-7)			
<b>Aquatic</b>			
Crustacea	EC50	Tubificid worm (Tubifex tubifex)	28.61 - 38.03 mg/l, 48 hours
Ethylbenzene (CAS 100-41-4)			
<b>Aquatic</b>			
Crustacea	EC50	Water flea (Daphnia magna)	1.37 - 4.4 mg/l, 48 hours
Fish	LC50	Fathead minnow (Pimephales promelas)	7.5 - 11 mg/l, 96 hours
Methyl Acetate (CAS 79-20-9)			
<b>Aquatic</b>			
Fish	LC50	Fathead minnow (Pimephales promelas)	295 - 348 mg/l, 96 hours
Styrene (CAS 100-42-5)			
<b>Aquatic</b>			
Crustacea	EC50	Water flea (Daphnia magna)	3.3 - 7.4 mg/l, 48 hours
Fish	LC50	Sheepshead minnow (Cyprinodon variegatus)	5.1 - 16 mg/l, 96 hours
Titanium Dioxide (CAS 13463-67-7)			
<b>Aquatic</b>			
Crustacea	EC50	Water flea (Daphnia magna)	> 1000 mg/l, 48 hours
Fish	LC50	Mummichog (Fundulus heteroclitus)	> 1000 mg/l, 96 hours
Toluene (CAS 108-88-3)			
<b>Aquatic</b>			
Crustacea	EC50	Water flea (Daphnia magna)	5.46 - 9.83 mg/l, 48 hours
Fish	LC50	Coho salmon, silver salmon (Oncorhynchus kisutch)	8.11 mg/l, 96 hours
Xylene (CAS 1330-20-7)			
<b>Aquatic</b>			
Fish	LC50	Bluegill (Lepomis macrochirus)	7.711 - 9.591 mg/l, 96 hours

\* Estimates for product may be based on additional component data not shown.

**Persistence and degradability****Bioaccumulative potential****Partition coefficient n-octanol / water (log Kow)**

Ethylbenzene	3.15
Methyl Acetate	0.18

**Partition coefficient n-octanol / water (log Kow)**

Styrene	2.95
Toluene	2.73
Xylene	3.12 - 3.2

**Mobility in soil** No data available.

**Other adverse effects** No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.

### 13. Disposal considerations

<b>Disposal instructions</b>	Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Do not allow this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose of contents/container in accordance with local/regional/national/international regulations.
<b>Local disposal regulations</b>	Dispose in accordance with all applicable regulations.
<b>Hazardous waste code</b>	The waste code should be assigned in discussion between the user, the producer and the waste disposal company.
<b>Waste from residues / unused products</b>	Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).
<b>Contaminated packaging</b>	Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal.

### 14. Transport information

The following transportation information is provided based on the manufacturer's interpretation of shipping regulations. Each shipper is responsible for identifying, naming, marking, and labeling prior to offering for transport.

<b>DOT</b>	
<b>UN number</b>	UN1263
<b>UN proper shipping name</b>	Paint related material including paint thinning, drying, removing, or reducing compound
<b>Transport hazard class(es)</b>	
<b>Class</b>	3
<b>Subsidiary risk</b>	-
<b>Label(s)</b>	3
<b>Packing group</b>	II
<b>Special precautions for user</b>	Read safety instructions, SDS and emergency procedures before handling.
<b>Special provisions</b>	149, B52, IB2, T4, TP1, TP8, TP28
<b>Packaging exceptions</b>	150
<b>Packaging non bulk</b>	173
<b>Packaging bulk</b>	242
<b>IATA</b>	
<b>UN number</b>	UN1263
<b>UN proper shipping name</b>	Paint related material (including paint thinning or reducing compounds)
<b>Transport hazard class(es)</b>	
<b>Class</b>	3
<b>Subsidiary risk</b>	-
<b>Packing group</b>	II
<b>Environmental hazards</b>	No.
<b>ERG Code</b>	3L
<b>Special precautions for user</b>	Read safety instructions, SDS and emergency procedures before handling.
<b>Other information</b>	
<b>Passenger and cargo aircraft</b>	Allowed with restrictions.
<b>Cargo aircraft only</b>	Allowed with restrictions.
<b>IMDG</b>	
<b>UN number</b>	UN1263
<b>UN proper shipping name</b>	PAINT (including paint, lacquer, enamel, stain, shellac, varnish, polish, liquid filler and liquid lacquer base) or PAINT RELATED MATERIAL (including paint thinning or reducing compound)
<b>Transport hazard class(es)</b>	
<b>Class</b>	3
<b>Subsidiary risk</b>	-
<b>Packing group</b>	II

**Environmental hazards****Marine pollutant**

No.

**EmS**

F-E, S-E

**Special precautions for user**

Read safety instructions, SDS and emergency procedures before handling.

**Transport in bulk according to  
Annex II of MARPOL 73/78 and  
the IBC Code**

Not established.

DOT



IATA; IMDG

**15. Regulatory information****US federal regulations**

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

**TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)**

Tremolite (Non-asbestiform) (CAS 14567-73-8)

0.1 % Annual Export Notification required.

**CERCLA Hazardous Substance List (40 CFR 302.4)**

Barium Sulfate (CAS 7727-43-7)

Listed.

Ethylbenzene (CAS 100-41-4)

Listed.

Methyl Acetate (CAS 79-20-9)

Listed.

Styrene (CAS 100-42-5)

Listed.

Toluene (CAS 108-88-3)

Listed.

Tremolite (Non-asbestiform) (CAS 14567-73-8)

Listed.

Xylene (CAS 1330-20-7)

Listed.

**SARA 304 Emergency release notification**

Not regulated.

**OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)**

Tremolite (Non-asbestiform) (CAS 14567-73-8)

Cancer  
Lung**Superfund Amendments and Reauthorization Act of 1986 (SARA)****Hazard categories**

Immediate Hazard - Yes

Delayed Hazard - Yes

Fire Hazard - Yes

Pressure Hazard - No

Reactivity Hazard - No

**SARA 302 Extremely hazardous substance**

Not listed.

**SARA 311/312 Hazardous  
chemical**

No

**SARA 313 (TRI reporting)**

Chemical name	CAS number	% by wt.
Ethylbenzene	100-41-4	5 - < 10
Styrene	100-42-5	< 1
Toluene	108-88-3	10 - < 20
Tremolite (Non-asbestiform)	14567-73-8	< 1
Xylene	1330-20-7	20 - < 30

**Other federal regulations****Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List**

Ethylbenzene (CAS 100-41-4)  
 Styrene (CAS 100-42-5)  
 Toluene (CAS 108-88-3)  
 Tremolite (Non-asbestiform) (CAS 14567-73-8)  
 Xylene (CAS 1330-20-7)

**Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)**

Not regulated.

**Safe Drinking Water Act (SDWA)**

Not regulated.

**Drug Enforcement Administration (DEA). List 2, Essential Chemicals (21 CFR 1310.02(b) and 1310.04(f)(2) and Chemical Code Number**

Toluene (CAS 108-88-3) 6594

**Drug Enforcement Administration (DEA). List 1 & 2 Exempt Chemical Mixtures (21 CFR 1310.12(c))**

Toluene (CAS 108-88-3) 35 %WV

**DEA Exempt Chemical Mixtures Code Number**

Toluene (CAS 108-88-3) 594

**FEMA Priority Substances Respiratory Health and Safety in the Flavor Manufacturing Workplace**

Methyl Acetate (CAS 79-20-9) Low priority  
 Styrene (CAS 100-42-5) Other Flavoring Substances with OSHA PEL's

**US state regulations**

WARNING: This product contains a chemical known to the State of California to cause cancer and birth defects or other reproductive harm.

**US - California Proposition 65 - CRT: Listed date/Carcinogenic substance**

Carbon Black (CAS 1333-86-4) Listed: February 21, 2003  
 Crystalline Quartz (CAS 14808-60-7) Listed: October 1, 1988  
 Ethylbenzene (CAS 100-41-4) Listed: June 11, 2004  
 Styrene (CAS 100-42-5) Listed: April 22, 2016  
 Titanium Dioxide (CAS 13463-67-7) Listed: September 2, 2011  
 Tremolite (Non-asbestiform) (CAS 14567-73-8) Listed: February 27, 1987

**US - California Proposition 65 - CRT: Listed date/Developmental toxin**

Toluene (CAS 108-88-3) Listed: January 1, 1991

**US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd. (a))**

Carbon Black (CAS 1333-86-4)  
 Crystalline Quartz (CAS 14808-60-7)  
 Ethylbenzene (CAS 100-41-4)  
 Styrene (CAS 100-42-5)  
 Talc (CAS 14807-96-6)  
 Titanium Dioxide (CAS 13463-67-7)  
 Toluene (CAS 108-88-3)  
 Tremolite (Non-asbestiform) (CAS 14567-73-8)  
 Xylene (CAS 1330-20-7)

**International Inventories**

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	No
Canada	Domestic Substances List (DSL)	No
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	No
Europe	European List of Notified Chemical Substances (ELINCS)	No

Country(s) or region	Inventory name	On inventory (yes/no)*
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	No

\*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)  
A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

## 16. Other information, including date of preparation or last revision

<b>Issue date</b>	03-09-2017
<b>Version #</b>	01
<b>Disclaimer</b>	Performer Series cannot anticipate all conditions under which this information and its product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use.
<b>Revision information</b>	This document has undergone significant changes and should be reviewed in its entirety.